

PRODUCT INFORMATION

ALUMINUM BASE CHANNEL

- Solid 6061 aluminum alloy
- Temper T5
- Baked on polyester paint or powder coated finish
- 3/4" x 3/4", 8' or 12' in length

PVC VINYL CAP:

- Window grade virgin vinyl with UV inhibitor
- 3/8" x 1/2", 8' or 12' in length
- Long Term High Temperature Exposure: Under certain conditions, the cap can be affected by reaching an internal temperature of 160°F. Long term exposure at 160°F can cause the shape to change and become ineffective as intended. This can and has happened on a very limited basis. This has occurred primarily with the black cap in extreme conditions. If you are in an area with high UV, west setting sun and little or no UV filter we caution against an Exterior Corner Mount using the Bronze/Black color. If Bronze/Black is your only option, we strongly recommend an Inside [Flush Mount](#) to protect the cap from direct sun.

SAND SCREWS

- High tensile strength carbon steel metal to wood fastener
- #9 thread
- 1 ¼" in length
- Star drive T-25 bit
- Tech/drill design for easy penetration
- High/low thread
- Climatek coating approved by the ICC against corrosion
- Color coordinated with SCREENEZE®

BRONZE, WHITE & CLAY SCREWS

- High tensile strength carbon steel metal to wood fastener
- #10 thread
- 1 ¼" in length
- #8 size head
- Square drive #2 bit
- Tech/drill design for easy penetration through metal
- High thread for faster drilling
- 1000 hour ACQ approved coating
- Color coordinated with SCREENEZE®

all screws will be square drive by end of 2017